

RSP2 stylus carrying capability

UCCsuite version	Stylus Ø x Length	Stem Material	Ball Material	RSH175	RSH250	RSH350	RSH450	RSH500
				4.4.8	4.4.8	4.4.8	4.4.8	4.4.5
A-5000-7805	0.5x10	TC	R	✓	✓	✗	✗	✗
A-5003-1345	0.5x20	TC	R	✗	✓	✗	✗	✗
A-5003-0577	0.7x20	TC	R	✓	✗	✗	✗	✗
A-5003-4890	1x10	SS	R	✓	✓	✓	✗	✗
A-5000-7806	1x10	SS	R	✓	✓	✓	✗	✗
A-5003-0033	1x20	TC	R	✓	✓	✗	✗	✗
A-5000-7808	1x20	TC	R	✓	✓	✗	✗	✗
A-5000-8663	1x27	TC	R	✗	✓	✗	✗	✗
A-5003-0035	1.5x30	TC	R	✓	✓	✗	✗	✗
A-5000-7807	2x10	SS	R	✓	✓	✓	✗	✗
A-5003-3822	2x20	TC	R	✓	✗	✗	✗	✗
A-5000-7812	2x20	SS	R	✗	✓	✓	✗	✗
A-5000-3603	2x20	SS	R	✗	✓	✓	✓	✓
A-5003-1730	2x20	SS	SN	✗	✓	✓	✓	✓
A-5003-0036	2x30	TC	R	✗	✓	✗	✗	✓
A-5003-7573	2x30	TC	SN	✗	✓	✗	✗	✓
A-5003-0037	2x40	TC	R	✓	✓	✗	✗	✓
A-5003-7269	2x40	TC	SN	✓	✓	✗	✗	✓
A-5000-3604	3x10	SS	R	✓	✓	✗	✗	✗

A-5000-4160	3x20	SS	R	✓	✓	✗	✗	✗
A-5003-7852	3x30	CF	R	✓	✓	✗	✗	✗
A-5003-3877	3x40	CF	R	✗	✓	✗	✗	✗
A-5003-0064	3x50	CE	R	✗	✓	✗	✗	✓
A-5000-4154	4x10	SS	R	✓	✓	✓	✗	✗
A-5000-4161	4x20	SS	R	✗	✓	✗	✗	✗
A-5003-0073	4x20	SS	R	✗	✓	✗	✗	✗
A-5555-0313	4x22	TC	R	✓	✗	✗	✗	✗
A-5003-1029	4x22	TC	R	✓	✗	✗	✗	✗
A-5003-0045	4x50	TC	R	✓	✗	✗	✗	✗
A-5003-0065	4x50	CE	R	✗	✓	✗	✗	✗
A-5000-4155	5x10	SS	R	✗	✓	✓	✗	✗
A-5004-1765	5.5x10	SS	R	✗	✓	✗	✗	✗
A-5000-4156	6x10	SS	R	✓	✓	✓	✓	✓
A-5003-2287	6x50	CF	R	✗	✗	✓	✗	✓
A-5000-4158	8x11	SS	R	✓	✗	✓	✗	✗
A-5000-3614 (Hemisphere)	18	CE	R	✓	✗	✗	✗	✗

NOTE:

The RSP2 cannot be used with stylus extensions or cranked configurations.

- CE-Ceramic,
- SS-Stainless Steel,
- CF-Carbon Fibre,
- TC-Tungsten Carbide
- SN-Silicon Nitride